PUREBev 7630



Tube	White Butyl, phthalates free
Temperature	-40°F / +248°F (-40°C / +120°C)
Reinforcement	Synthetic plies, galvanized wire helices
Cover	Smooth, red, cloth finish. Resistant to abrasion, ageing and ozone.
Sterilization	Refer to Parker's guidelines for cleaning and sanitizing.
ISO 1307	For dimensional tolerances.
Applications	Beer, wine and consumable liquids

# Part Number		ose D	Hose O.D.		Vacuum		Max. Working Pressure		Min. Burst Pressure		kg Weight		Rend Radius	
	in	mm	in	mm	in of Hg	kPa	psi	bar	psi	bar	lbs/ft	kg/m	in	mm
7630-1000	1	25	1.5	40	26.5	90	250	16	750	48	0.69	1.03	3.94	100
7630-1500	1.5	38	2.09	53	26.5	90	250	16	750	48	1.01	1.51	6.10	155
7630-2000	2	51	2.6	66	26.5	90	250	16	750	48	1.31	1.96	8.46	215
7630-2500	2.5	63.5	3.19	81	26.5	90	250	16	750	48	2.02	3.02	10.83	275
7630-3000	3	76	3.7	94	26.5	90	250	16	750	48	2.63	3.92	12.99	330
7630-4000	4	102	4.72	120	26.5	90	250	16	750	48	3.52	5.26	17.72	450

WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

All PUREBev hoses comply with the following standards: FDA

















PUREBev 7630P



Tube	White Butyl, phthalates free
Temperature	-40°F / +248°F (-40°C / +120°C)
Reinforcement	Synthetic plies, galvanized wire helices
Cover	Wide corrugated, red, low friction material, non-marking when dragged on the floor, easy to clean, glossy. Resistant to abrasion, ageing, ozone, oil and chemicals.
Sterilization	Refer to Parker's guidelines for cleaning and sanitizing.
ISO 1307	For dimensional tolerances.
Applications	Beer, wine and consumable liquids

# Part Number		ose D	Hose O.D.		Vacuum		Max. Working Pressure		Min. Burst Pressure		kg Weight		**************************************	
	in	mm	in	mm	in of Hg	kPa	psi	bar	psi	bar	lbs/ft	kg/m	in	mm
7630P-1000	1	25.4	1.5	38	26.5	90	250	16	900	60	0.61	0.91	4.13	105
7630P-1500	1.5	38	2.07	52.5	26.5	90	250	16	900	60	0.92	1.38	4.72	120
7630P-2000	2	51	2.64	67	26.5	90	250	16	900	60	1.48	2.21	5.91	150
7630P-2500	2.5	63.5	3.17	80.5	26.5	90	250	16	900	60	1.87	2.79	7.68	195
7630P-3000	3	76	3.7	94	26.5	90	250	16	900	60	2.35	3.51	8.86	225

WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.













