



PUREspirits 7650P



Tube	White UHMWPE, phthalates free
Temperature	-31°F / +212°F (-35°C / +100°C)
Reinforcement	Synthetic plies, galvanized wire helices
Cover	Wide corrugated, green, low friction material, non-marking when dragged on the floor, easy to clean, glossy. Abrasion, ageing, ozone, oil and chemical resistant.
Sterilization	Refer to Parker's guidelines for cleaning and sanitizing.
ISO 1307	For dimensional tolerances.
Applications	Spirits, beer, wine and chemicals

# Part Number	Hose ID		Hose O.D.		Vacuum		Max. Working Pressure		Min. Burst Pressure		Weight		Bend Radius	
	in	mm	in	mm	in of Hg	kPa	psi	bar	psi	bar	lbs/ft	kg/m	in	mm
7650P-0750	.75	19	1.25	31.5	26.5	90	150	10	450	30	0.60	0.89	4.33	110
7650P-1000	1	25.4	1.46	37	26.5	90	150	10	450	30	0.54	0.80	3.94	100
7650P-1500	1.5	38	1.97	50	26.5	90	150	10	450	30	0.76	1.14	5.91	150
7650P-2000	2	51	2.56	65	26.5	90	150	10	450	30	1.21	1.81	7.87	200
7650P-3000	3	76	3.58	91	26.5	90	150	10	450	30	1.88	2.81	13.78	350
7650P-4000	4	102	4.61	117	26.5	90	150	10	450	30	2.46	3.67	19.69	500

WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

All PUREspirits hoses comply with the following standards:

