## PURE PTFE 7660



Tube	Clear PTFE
Temperature	-40°F / +302°F (-40°C / +150°C)
Reinforcement	Synthetic plies, stainless steel wire helices, a/s wire to discharge static electricity.
Cover	Smooth, white cloth finish. Resistant to abrasion, ageing and ozone.
Sterilization	Refer to Parker's guidelines for cleaning and sanitizing.
ISO 1307	For dimensional tolerances.
Applications	Various chemicals, cosmetics, pharmaceutical materials

#	(	•	(	0	E			2)	کے	<u></u>	_	9	-	9
Part Number		ose D	Hose O.D.		Vacuum		Max. Working Pressure		Min. Burst Pressure		Weight		Bend Radius	
	in	mm	in	mm	in of Hg	kPa	psi	bar	psi	bar	lbs/ft	kg/m	in	mm
7660-0500	.50	13	1	25	26.5	90	250	16	1000	64	0.34	0.50	2.95	75
7660-0750	.75	19	1.22	31	26.5	90	250	16	1000	64	0.34	0.51	4.33	110
7660-1000	1	25	1.46	37	26.5	90	250	16	1000	64	0.44	0.66	5.91	150
7660-1500	1.5	38	2	51	26.5	90	250	16	1000	64	0.74	1.11	9.45	240
7660-2000	2	50	2.6	64	26.5	90	250	16	1000	64	0.90	1.35	12.6	320

WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

PUREPTFE 7660 hose complies with the following standards: FDA CE CE

















## PUREPTFE 7660P



Tube	Black PTFE, conductive
Temperature	-40°F / +302°F (-40°C / +150°C)
Reinforcement	Synthetic plies, stainless steel wire helices, a/s wire to discharge static electricity.
Cover	Corrugated, white with conductive chips, low friction material, non-marking when dragged on the floor, easy to clean, glossy. Resistant to oil, chemical, abrasion, ageing and ozone. Meets FDA 21 cfr 177.1520.
Sterilization	Refer to Parker's guidelines for cleaning and sanitizing.
EN12115	
Applications	Various chemicals, cosmetics, pharmaceutical materials

# Part Number		ose D	Hose O.D.		Vacuum		Max. Working Pressure		Min. Burst Pressure		□ C [kg] Weight		#N Bend Radius	
	in	mm	in	mm	in of Hg	kPa	psi	bar	psi	bar	lbs/ft	kg/m	in	mm
7660P-0500	.50	13	1	25	26.5	90	150	10	600	40	0.33	0.49	2.76	70
7660P-0750	.75	19	1.22	31	26.5	90	150	10	600	40	0.43	0.64	3.94	100
7660P-1000	1	25	1.46	37	26.5	90	150	10	600	40	0.53	0.79	5.12	130
7660P-1500	1.5	38	2	51	26.5	90	150	10	600	40	0.83	1.24	7.48	190
7660P-2000	2	50	2.6	64	26.5	90	150	10	600	40	1.23	1.84	9.84	250



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.











